

Gas 1	Gas 2	Code	Code	Typische Werte für		Typische Werte für		Typische Integrationszeit	Spülmodus		Spülmedium
				Temperatur	Druck	Weglänge	Staubbelastung		Standard	Optional	
O ₂		A	A	< 150 °C	1000 hPa	1 ... 6 m	< 100 mg/Nm ³	30 s	D	B	N ₂
NH ₃		C		< 150 °C	1000 hPa	1 ... 6 m	< 100 mg/ Nm ³	30 s	C	G	Luft
NH ₃	H ₂ O	D		< 150 °C	1000 hPa	1 ... 6 m	< 100 mg/Nm ³	30 s	C	G	Luft
HCl		E		< 150 °C	1000 hPa	1 ... 6 m	< 100 mg/ Nm ³	30 s	C	G	Luft
HCl	H ₂ O	F		< 150 °C	1000 hPa	1 ... 6 m	< 100 mg/Nm ³	30 s	C	G	Luft
HF		G		< 150 °C	1000 hPa	1 ... 6 m	< 100 mg/ Nm ³	30 s	C	G	Luft
HF	H ₂ O	H		< 150 °C	1000 hPa	1 ... 6 m	< 100 mg/ Nm ³	30 s	C	G	Luft
CO ₂ ¹⁾		L		< 150 °C	1000 hPa	1 ... 6 m	< 100 mg/ Nm ³	30 s	C	G	Luft
H ₂ O ¹⁾		M		< 150 °C	1000 hPa	1 ... 6 m	< 100 mg/ Nm ³	30 s	C	G	Luft
O ₂		A	B	600 ... 1200 °C	1000 hPa	2 ... 6 m	< 20 g/Nm ³	10 s	E, F	G, H	Dampf + Luft, N ₂
O ₂	Temp.	B		600 ... 1200 °C	1000 hPa	2 ... 6 m	< 20 g/ Nm ³	10 s	F	H	Dampf + N ₂
CO		J		< 600 °C	1000 hPa	1 ... 6 m	< 20 g/ Nm ³	10 s	E	G	Luft
O ₂		A	C	< 150 °C	1000 hPa	1 ... 6 m	< 100 mg/ Nm ³	2 s	D	B	N ₂
CO		J		< 150 °C	1000 hPa	1 ... 4 m	< 20 g/ Nm ³	2 s	E	G	Luft oder N ₂
O ₂		A	D	< 150 °C	1000 hPa	1 ... 6 m	< 100 mg/Nm ³	10 s	D	B	N ₂
CO		J		< 600 °C	1000 hPa	1 ... 4 m	< 20 g/ Nm ³	2 s	E	G	Luft oder N ₂
NH ₃		C	E	250 ... 350 °C	1000 hPa	2 ... 6 m	< 20 g/ Nm ³	30 s	E	G	Luft
NH ₃	H ₂ O	D		250 ... 350 °C	1000 hPa	2 ... 6 m	< 20 g/ Nm ³	30 s	E	G	Luft
NH ₃		C	F	300 ... 400 °C	1000 hPa	4 ... 8 m	< 20 g/ Nm ³	30 s	E	G	Luft
NH ₃	H ₂ O	D		300 ... 400 °C	1000 hPa	4 ... 8 m	< 20 g/ Nm ³	30 s	E	G	Luft
NH ₃		C	G	20 ... 650 °C	1000 hPa	1 m	< 2 g/ Nm ³	2 s	C	A	Luft
NH ₃	H ₂ O	D		20 ... 650 °C ¹⁾	1000 hPa	1 m	< 2 g/ Nm ³	2 s	C	A	Luft
HCl		E	H	150 ... 250 °C	1000 hPa	1 ... 6 m	< 20 g/ Nm ³	10 s	E	G	Luft
HCl	H ₂ O	F		150 ... 250 °C	1000 hPa	1 ... 6 m	< 20 g/ Nm ³	10 s	E	G	Luft
HF		G		150 ... 250 °C	1000 hPa	1 ... 6 m	< 20 g/ Nm ³	10 s	E	G	Luft
HF	H ₂ O	H		150 ... 250 °C	1000 hPa	1 ... 2 m	< 20 g/ Nm ³	10 s	E	G	Luft
H ₂ O		M	J	< 150 °C	1000 hPa	1 ... 2 m	< 100 g/ Nm ³	2 s	B	D	N ₂ , trocken ²⁾

Referenztafel: Standardkombinationen (Fortsetzung)

1) Für Temperatur über 400 °C bitte kontaktieren Sie Siemens.

2) Taupunkt < -80 °C.